

**METHOD FOR PRODUCING FLUORESCENT SUBSTANCE,
FLUORESCENT SUBSTANCE PRODUCED BY THE METHOD, AND
DEVICE, ELECTRONIC INSTRUMENT AND FLUORESCENT
SUBSTANCE-CONTAINING ARTICLE USING THE FLUORESCENT
SUBSTANCE**

Patent Number: JP2000297279
Publication date: 2000-10-24
Inventor(s): OSHIO SHOZO;; SHIGETA TERUAKI;; MATSUOKA TOMIZO
Applicant(s): MATSUSHITA ELECTRIC IND CO LTD
Requested Patent: ☐ JP2000297279
Application Number: JP19990106987 19990414
Priority Number(s):
IPC Classification: C09K11/08
EC Classification:
Equivalents:

Abstract

PROBLEM TO BE SOLVED: To provide a method for producing a fluorescent substance capable of efficiently producing a fluorescent substance having objective particle diameters.

SOLUTION: A fluorescent substance 1 having an objective particle diameter is obtained as follows: a starting material for fluorescent substance comprising an adhered-substance raw material 4, which is to form an adhered substance 2, and a small-granular raw material 3, which is to form the fluorescent substance 1, is mixed; the mixed starting material for fluorescent substance is subjected to a reaction to form a fluorescent substance 1 having a state where the fluorescent substance 1 is attached on an formed adhered substance 2; the attached fluorescent substance 1 is peeled from the adhered substance 2; and subsequently, the peeled fluorescent substance 1 is separated from the adhered substance 2 to obtain the fluorescent substance 1 having objective particle diameters. α -Alumina single crystals having substantially no crushed surface are preferable as the small-granular raw material 3, and the central particle diameter preferably ranges from 0.1 to 20 μ m. The central particle diameter of the adhered substance 2 is preferably larger than the central particle diameter of the attached fluorescent substance 1, and is 50 μ m or less.

Data supplied from the esp@cenet database - I2